


Hahn
KT-N 6R
KT-V 6R
KT-EN



Application area For PVC U profiles Housing Public building	✓ ✓ ✓	✓ ✓ ✓	✓ ✓ x
Material Extruded aluminum profiles	✓	✓	✓
Size Width Height	 99 mm 112 mm	106 mm 112 mm	102.5 mm 97 mm
Weight capacity / resistance	160 kg	160 kg	120 kg
Maintenance free	✓	✓	✓
Color options RAL-colors	✓	✓	✓
Fastening High degree of pre-mounted parts KT-Fix Direct Fastening/standard screws/self drilling screws For left hand and right hand doors No interruption of gasket Additional lateral fixing in upstand	✓ ✓ ✓/x ✓ ✓ ✓	✓ ✓ ✓/x ✓ ✓ x	✓ x ✓/✓ ✓ ✓ ✓
Upstand ranges 15–20 mm 16.5–21.5 mm 18–23 mm 20–25 mm 22–27 mm	✓ ✓ ✓ ✓ ✓	✓ ✓ ✓ ✓ ✓	✓ ✓ ✓ x ✓
Special version for narrow and very narrow frames	x	x	x
Regulation Regulation by only 1 person In 6 directions without removing sash Without modification of esthetics Horizontal regulation Vertical regulation Sealing compression adjustment continuously ±2,5 mm/+0,5 mm additional in upstand range	✓ ✓ ✓ continuously ±5 mm continuously +4/-3 mm ✓/✓	✓ ✓ ✓ continuously ±5 mm continuously +4/-3 mm ✓/✓	✓ ✓ ✓ continuously ±5 mm continuously +3/-2 mm ✓/x
Certification CE-Certification according to EN 1935:2002 SKG	✓ 2 stars	✓ 2 stars	✓ 2 stars